

	AG- DM825GF
50Hz	260KW 325KVA
50Hz	240KW 300KVA



- DCOSAN P126TI -
- 40°C
- 24V
- :
- I P23 H
- 
- 
- 
- 
- 12V
- 
- 



V	Hz		COS	A	KW/KVA	KW/KVA
254/440	50	3	0.8	433	264/330	240/300
240/415	50	3	0.8	459	264/330	240/300
230/400	50	3	0.8	476	264/330	240/300
220/380	50	3	0.8	501	264/330	240/300

GB/T2820-97 eqv I SO8528

1 10%

12







GB755, BS5000, VDE0530, NEMMG1-22, IEC34-1, CSA22 2 AS1359



:	/
	3
	Y
	1
	0.8
	IP23
	1000m
/	H/H
TIF	50
THF	2%
	300KVA
	93.0%
	0.8m³/s



	± 5%
	± 1%
100%	+25%
	-20%
	6S
	1%
	5%
	1.5%
100%	+12%
	-10%
	5S

苏州



标准型机组控制屏是满足机组正常操作、使用的最基本配置，具有操作简便、功能齐全、保护可靠等优点。功能特点：采用众智控制器； 显示屏；机组具有手动开机、关机（急停）等控制功能，具有油压低、水温高、超速、电压高、电压低、过流等多种保护功能，可满足各种机组的需要。



ATS

