

Diesel Generator Set
Exclusively from your Cat® dealer

Image shown may not reflect actual package

Output Ratings		
Generating Set Model - 3 Phase	Prime*	Standby*

* Refer to ratings definitions on page 4.
 Ratings at _____ power factor.

Technical Data		
Engine Make & Model:		
Alternator Model:		
Control Panel:		
Base Frame Type:	Heavy Duty Fabricated Steel	
Circuit Breaker Type:		
Frequency:	50 Hz	60 Hz
Engine Speed: RPM		
Fuel Tank Capacity: litres (US gal)		
Fuel Consumption, Prime: l/hr (US gal/hr)		
Fuel Consumption, Standby : l/hr (US gal/hr)		



Engine Technical Data

Physical Data	
Manufacturer:	Perkins
Model:	1306A-E87TAG6
No. of Cylinders/Alignment:	6 / In Line
Cycle:	4 Stroke
Induction:	Turbocharged Air To Air Charge Cooled
Cooling Method:	Water
Governing Type:	Electronic
Governing Class:	ISO 8528 G2
Compression Ratio:	16.9:1
Displacement: l (cu.in)	8.7 (530.9)
Bore/Stroke: mm (in)	116.6 (4.6)/135.9 (5.4)
Moment of Inertia: kg m² (lb. in²)	1.54 (5266)
Engine Electrical System:	
-Voltage/Ground:	24/Negative
-Battery Charger Amps:	50
Weight: kg (lb) - Dry:	671 (1479)
- Wet:	698 (1539)

Air System	50 Hz	60 Hz
Air Filter Type:	Paper Element	
Combustion Air Flow:		
m ³ /min (cfm) -Standby:	18.6 (657)	-
-Prime:	17.4 (614)	-
Max. Combustion Air Intake		
Restriction: kPa (in H ₂ O)	6.2 (25.0)	-
Radiator Cooling Air Flow:		
m ³ /min (cfm)	349.8 (12353)	-
External Restriction to		
Cooling Air Flow: Pa (in H ₂ O)	125 (0.5)	-

Cooling System	50 Hz	60 Hz
Cooling System Capacity:		
l (US gal)	24.7 (6.5)	-
Water Pump Type:	Centrifugal	
Heat Rejected to Water & Lube Oil: kW (Btu/min)		
-Standby:	99.0 (5630)	-
-Prime:	96.0 (5459)	-
Heat Radiation to Room: Heat radiated from engine and alternator		
kW (Btu/min) -Standby:	29.3 (1666)	-
-Prime:	24.3 (1382)	-
Radiator Fan Load: kW (hp)	9.9 (13.3)	-

Cooling system designed to operate in ambient conditions up to 50°C (122°F). Contact your local Olympian™ dealer for power ratings at specific site conditions.

Lubrication System	
Oil Filter Type:	Spin-On, Full Flow
Total Oil Capacity l (US gal):	26.5 (7.0)
Oil Pan l (US gal):	22.7 (6.0)
Oil Type:	API CI-4
Cooling Method:	Water

Performance	50 Hz	60 Hz
Engine Speed: RPM	1500	-
Gross Engine Power: kW (hp)		
-Standby:	250.0 (335.0)	-
-Prime:	228.0 (306.0)	-
BMEP: kPa (psi)		
-Standby:	2297.0 (333.2)	-
-Prime:	2095.0 (303.8)	-
Regenerative Power: kW	20.8	-

Fuel System				
Fuel Filter Type:	Replaceable Element			
Recommended Fuel:	Class A2 Diesel or BSEN590			
Fuel Consumption: l/hr (US gal/hr)				
	110% Load	100% Load	75% Load	50% Load
Prime				
50 Hz	58.8 (15.5)	54.2 (14.3)	43.0 (11.4)	31.9 (8.4)
60 Hz	-	-	-	-
Standby				
50 Hz		58.8 (15.5)	46.4 (12.3)	34.1 (9.0)
60 Hz		-	-	-

(based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)

Exhaust System	50 Hz	60 Hz
Silencer Type:	Industrial	
Silencer Model & Quantity:	SD100 (1)	
Pressure Drop Across		
Silencer System: kPa (in Hg)	8.70 (2.569)	-
Silencer Noise Reduction		
Level: dB	12	-
Max. Allowable Back		
Pressure: kPa (in. Hg)	10.7 (3.2)	-
Exhaust Gas Flow:		
m ³ /min (cfm) -Standby:	44.5 (1572)	-
-Prime:	40.5 (1430)	-
Exhaust Gas Temperature: °C (°F)		
-Standby:	579 (1074)	-
-Prime:	526 (979)	-

Alternator Performance Data

Data Item	50 Hz				60 Hz				
	415/240V	400/230V 230/115V 200/115V	380/220V 220/110V	220/127V					
Motor Starting Capability* kVA	495	465	425	546					
Short Circuit Capacity** %	300	300	300	300					
Reactances: Per Unit									
Xd	2.096	3.258	3.610	2.315					
X'd	0.138	0.155	0.171	0.110					
X''d	0.083	0.093	0.103	0.066					

Reactances shown are applicable to prime ratings.

*Based on 30% voltage dip at 0.6 power factor.

** With optional Permanent Magnet generator or AREP excitation.

Alternator Technical Data

Physical Data	
Manufactured for Olympian by:	OLYMPIAN
Model:	LL5014H
No. of Bearings:	1
Insulation Class:	H
Winding Pitch - Code:	2/3 - 6
Wires:	12
Ingress Protection Rating:	IP23
Excitation System:	SHUNT
AVR Model:	R250

Operating Data	
Overspeed: RPM	2250
Voltage Regulation: (steady state)	+/- 0.5%
Wave Form NEMA = TIF:	50
Wave Form IEC = THF:	2.0%
Total Harmonic Content LL/LN:	4.0%
Radio Interference:	Suppression is in line with European Standard EN61000-6
Radiant Heat: kW (Btu/min)	
-50 Hz:	19.3 (1098)
-60 Hz:	-

Technical Data



Voltage 50 Hz	Prime		Standby	
	kVA	kW	kVA	kW
415/240V	240.0	192.0	266.0	212.8
400/230V	250.0	200.0	275.0	220.0
380/220V	250.0	200.0	275.0	220.0
230/115V	250.0	200.0	275.0	220.0
220/127V	215.0	172.0	240.0	192.0
220/110V	250.0	200.0	275.0	220.0
200/115V	250.0	200.0	275.0	220.0

Voltage 60 Hz	Prime		Standby	
	kVA	kW	kVA	kW

Weights & Dimensions

Weights: kg (lb)	
Net (+ lube oil)	1942 (4281)
Wet (+ lube oil & coolant)	1964 (4330)
Fuel, lube oil & coolant	2356 (5194)

Dimensions: mm (in)	
Length	2662 (104.8)
Width	1030 (40.6)
Height	1760 (69.3)



Note: General configuration not to be used for installation. See general dimension drawings for detail.

Definitions

Standby Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

Prime Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) air inlet temp, 100m (328ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

General Data

Documents

A full set of operation and maintenance manuals and circuit wiring diagrams.

Quality Standards

The equipment meets the following standards: BS5000, ISO 8528, ISO 3046, IEC 60034, NEMA MG-1.22.

Warranty

All prime equipment carries a one year manufacturer's warranty. Standby equipment, limited to 500 running hours per year, has a two year manufacturer's warranty. For details on warranty cover please contact your local Dealer, or visit our website: www.OlympianPower.com.

Information contained in this publication may be considered confidential. Discretion is recommended when distributing.

www.OlympianPower.com

Market: International
LEHF0244-00 (09/14)

Materials and specifications are subject to change without notice. CAT, CATERPILLAR, their respective logos OLYMPIAN, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

© 2014 Caterpillar
All rights reserved.